



REDLINE APPARATUS OPERATOR SYSTEM



REDLINE™ LIBERATOR® IV

APPARATUS OPERATOR SINGLE COMMUNICATIONS SYSTEM

- » First of its kind multi-mode headset with Electronic Noise Compression and Active Noise Cancellation technology that protects hearing, while allowing clear communication in the noisiest environments
- » Ambient sound amplification for 360 degree situational awareness / face-to-face communication
- » High temperature durability (500°F for 5 minutes) and high temperature sustained operation
- » Dual-Fuel power options; 2-AAA's or 1-CR123, each offering 250 hours of operation
- » Noise canceling boom microphone for clear voice transmission, even when worn with SCBA
- » Low profile behind-the-head suspension, designed to fit under fire and rescue helmets, without interfering with the helmet ratchet adjustment. Over-the-head suspension available (pictured)
- » Does not interfere with SCBA face mask seal
- » Connectivity for most common public safety portable radios via Safariland® Fire Speaker Microphone (FSM)
- » Particulate dust and water spray resistant, submersible up to three (3) feet
- » Third party tested - explosive atmosphere certified, MILSTD certified and certified at 26 dB NRR
- » Easily cleaned / decontaminated

Designed, Manufactured, and Assembled in the United States

System includes Safariland® Fire Speaker Microphone (FSM)

SAFARILAND® REDLINE™

FIRE SPEAKER MICROPHONE (FSM) / PUSH-TO-TALK

- » Use as a stand-alone remote speaker microphone, or integrate with a Safariland® REDLINE™ Liberator® IV Headset
- » Extreme temperature durability (500°F for 5 minutes) as well as high temperature continuous operation
- » Also includes a listen only connector (monaural), compatible with any 1/8" or 3.5mm earbud
- » Available for all common public safety portable radios
- » Dual offset noise canceling microphones, positioned so they are never covered by gloved hands, for clear transmission at any direction in even the noisiest environment
- » Glow-in-the-dark reflective trim, for reference in low-light/dark conditions (see inset picture)
- » Large Emergency Activation Button (EAB) glows orange for quick location in low-light/dark conditions, and is easily activated with a gloved finger, while protected from accidental activations*
- » Particulate dust & water spray resistant, submersible to three (3') feet
- » Ergonomic design and large 2" ambidextrous tactile Push-to-Talk, allow ease of use with gloved hands and provides audible 'snap' feedback when engaged
- » Multi-attachment retention clip with D-ring rotates 360 degrees with eight (8) detents, compatible with PALS webbing, retention lanyards, and button clips (included)
- » Easily cleaned / decontaminated
- » Dimensions (mm): 86H x 72W x 31D (not including clip) Weight: 356g

Designed, Manufactured, and Assembled in the United States

**EAB available for NFPA 1802 MAP (jack) Connector Only*

